



DESCRIPTION

This product combines the features of vibration-proofing rubber commonly used for multi-screw, high frequency insulation, good sound-proofing function and decrement capability and those of metal springs low proper vibration. So it provides 3~4 times higher vibration-proofing efficiency than rubber pads. By lowering the center of gravity downwards to the maximum and maintaining correct load distribution, it offers uniform static deflection.

APPLICATION

- Vibration-proof for equipment for pumps, fans, FCU, AHU, Chiller.
- For industrial machinery (Press, Shearing machine etc.)
- For anchors and guides of riser pipes.
- For various other applications

DIMENSION & SELECTION GUIDE BY LOADS

TYPE	Capacity (kg)	Deflection (mm)	Dimension (mm)		
			A	B	H
SRP - 25	25	5.5	57	71	19
SRP - 50	50	5.5	57	71	19
SRP - 100	100	5.5	60	74	30
SRP - 200	200	5.5	60	74	30
SRP - 400	400	5.5	100	100	30
SRP - 600	600	5.5	100	100	30
SRP - 800	800	5.5	100	100	30
SRP - 1000	1,000	6.5	190	118	30
SRP - 1200	1,200	6.5	190	118	30
SRP - 1500	1,500	6.5	190	118	30
SRP - 2000	2,000	6.5	190	118	30



SEOUL OFFICE

1601-1, SEOCHO-DONG, SEOCH-GU, SEOUL, KOREA

TEL: +82 2 598 1988 FAX: +82 2 598 1989

Website : www.nsv.co.kr ; Email: overseas@nsv.co.kr

